
TECHNICAL DATA SHEET	Ultra Low Sag (ULS)	HVCRC® ULS 230 - 87 Epsilon Advanced Conductors	EPSILON CABLE
International size	**MONTE CARLO**		
ASTM Size	-		
Technical designation	ECRC® 230-AL0/87-X1		




Governing Units: Metric

STRANDING CONFIGURATION				
	*No. & Diameter of the core*		1 x 10.54	mm
	Aluminium layers construction / Height	28 TW x	2.56	mm
	1st layer composition and Øeq	12 x	3.20	mm
	2nd layer composition and Øeq	16 x	3.25	mm
	Lay Direction of outer layer		Right Hand (Z)	

CONDUCTOR PROPERTIES		
Cross Sectional Area - Annealed Aluminium	229.1	mm²
Cross Sectional Area - HVCRC Core	87.3	mm²
Total Area of Conductor Cross Section	316.4	mm²
Nominal equivalent Aluminium Area (1350-H19 at 61%IACS)	236.6	mm²
Overall Diameter of Conductor	20.78	mm
Mass per unit length - Annealed Aluminium	635.2	kg/km
Mass per unit length - Core	160.5	kg/km
Mass per unit length - Conductor	795.7	kg/km
Ultimate Tensile Strength of Conductor	239.3	kN
Core Rated Tensile Strength	225.6	kN
Coefficient of Linear Expansion **Above** Thermal Kneepoint	0.75	10^{-6} K^{-1}
Coefficient of Linear Expansion **Below** Thermal Kneepoint	11.81	10^{-6} K^{-1}
Final Modulus of Elasticity **Above** Thermal Kneepoint	146	GPa
Final Modulus of Elasticity **Below** Thermal Kneepoint	80	GPa

THERMAL SPECIFICATIONS		
Maximum Continuous Operating Temperature[2] (surface temperature)	180	°C
Maximum Emergency Temperature / 8760 Hours[2] (surface temperature)	200	°C
Thermal Heat Capacity for Annealed Aluminium Layers	606.6	W.s/m.°C
Thermal Heat Capacity for Composite Core	128.4	W.s/m.°C

ELECTRICAL SPECIFICATIONS		
Maximum DC Electrical Resistance at 20°C *(1370-O at 63%IACS)*	0.1225	Ω.km^{-1}
Temperature Coefficient of Resistance	4.03	10^{-3} K^{-1}
AC Nominal Resistance at 25°C (surface temperature)	0.1256	Ω.km^{-1}
AC Nominal Resistance at 75°C (surface temperature)	0.1502	Ω.km^{-1}
AC Nominal Resistance at 180°C (surface temperature)	0.2019	Ω.km^{-1}
AC Nominal Resistance at 200°C (surface temperature)	0.2118	Ω.km^{-1}
AC Current Rating at 180°C (surface temperature) [1]	1,107	A
AC Current Rating at 200°C (surface temperature) [1]	1,167	A



Geometric Mean Radius (GMR)	
8.87	mm
Inductive Reactance Ø0.3m radius	
0.222	Ω.km^{-1}
Capacitive Reactance Ø0.3m radius	
0.194	MΩ.km

(1) Ampacity calculations based on IEEE Standard 738-2012, according to the following data:

25 °C ambient temperature, *0.61 m/s wind velocity with an angle of 90 °,*

1000 W/m² solar radiation, *0.5 solar absorption coefficient,*

0.6 emissivity coefficient, *Resistance AC at 50 Hz current frequency.*

(2) Temperatures defined according to ASTM B987.

Reference standards for core properties: ASTM B987.

Reference standards for electrical specifications: IEC 62219.

Reference standards for stranding parameters: ASTM B857-14/IEC 62219.

Depending on conductor manufacturer rated specifications may slightly change.

Revision	*00*
Ref. Document	*ST25-00056*
Date	*14-Aug-2025*

This document is the property of EPSILON COMPOSITE

contact@epsilon-cable.com
www.epsilon-cable.com